

Tekron Time Code Generator TCG 02-E

A GPS clock with dual power supplies

The TCG 02-E is a highly accurate full featured GPS clock for use in electricity Distribution/Transmission and Generation protection and control systems. The TCG 02-E, like all Tekron clocks, also supports IEC 61850.



Features

- Remote Configuration
- Isolated singular or dual power supplies
- High drive power outputs
- Low noise characteristics due to balanced pair distribution
- UTC and LST with user defined DST options
- Master/ Slave function
- Second power supply option
- 9 outputs

Supports

- DC IRIG-B or Modified Manchester: TTL, RS232, RS422/ RS485, HV MOSFET
- AM IRIG-B (Modulated)
- Serial Strings
- User defined pulses
- DCF77
- NTP/ SNTP (IEC 61850)
- PTP (IEEE 1588 v2)
- Event Recording



About Tekron

Tekron International is a leading developer of exceedingly accurate GPS clocks and time synchronization solutions for use in industrial applications.

Tekron GPS clocks are simple to install and use and are extremely rugged, attributes that are a prerequisite in the often extreme environments in which the clocks are installed.

Tekron GPS clocks have been installed in thousands of power stations & substations across the globe, where they prove invaluable in assisting power companies to operate efficiently, minimizing downtime and increasing the accuracy of control decisions.

With a Tekron GPS clock you can be confident that you can set it up and walk away.

Physical

19" rack mount 1U high

(W) 430 mm x (D) 270 mm x (H) 45 mm, 2.0 Kg

IP40 (Ingress Protection rating)

Front panel display

The TCG 02-E has a 2 line x 16 character FSTN LCD display and two LEDs indicating multiple statuses, including:

- GPS Sync Status
- IRIG-B Sync Status
- Antenna cable fault
- Satellite acquisition mode

GPS Receiver

L1, C/ A code, 12 Channel Parallel-tracking receiver

Frequency:	1575.42 MHz	
Pulse accuracy:	15 ns	
Sensitivity:	Acquisition	-136 dBm
	Tracking	-141 dBm
Acquisition:	Hot Start	<18 s
	Warm Start	<45 s
	Cold Start	<50 s

Antenna

Physical

Conical shaped polycarbonate durable shell which minimizes snow and dust buildup.

Dimensions:	98 mm tall 90 mm diameter
Weight:	200 g

Specifications

Bandwidth:	1575.42 ± 1.023 MHz
Attenuation:	60 dB (typical) at 1575.42 ± 50 MHz
Gain:	38 dB 5 +/- 0.5 V (27 mA max)
Operating temperature:	-40 to 85° C

Antenna Cable

LMR240 ultra-flex low loss, high shielding antenna cable

Inputs & Outputs

2 x independently programmable outputs accurate to within 100ns of UTC, either:

- TTL 0 - 5 V, 150 mA (BNC or 2-pin)
- RS422 +/- 6 V, 50 loads (BNC or 2-pin)
- HV switch MOSFET 300 V 1 A (2-pin)
- Fiber TX (62.5/ 125 μm, λ 820 nm), compatible with multi-mode fiber (ST Fiber connectors)

Plus:

1 x RS232 serial port, DCE wired, Signals are +/- 10 V, 15 mA. Serial time messages output at 9600 baud. Programmable pulse on pin 1 (DB9).

Timing accuracy of RS232 port:

Serial Message	<200 μs to UTC
Pulse/ or IRIG-B time code	<1.5 μs to UTC

Plus:

1 x AM IRIG-B 9 Vpp, 50 ohm (BNC)
Timing accuracy: <2 μs to UTC

Plus:

2 x digital inputs: 0 - 5 V TTL/CMOS external IRIG-B synchronization

Plus:

1 x Sync Status Relay with NC/NO contacts

Plus:

2 x isolated digital inputs: 0-5 V TTL/CMOS

Plus:

1 x TTL Output (BNC) The signal output is the same as programmed on P4 Pin1

Timing accuracy: <100 ns to UTC

Plus:

4 x IRIG-B outputs (BNC) switchable between AM IRIG-B (B12x) or TTL (0 - 5 V , 25 mA) IRIG-B.

Timing accuracy TTL: <100 ns to UTC
Timing accuracy AM IRIG-B: <2 μs to UTC

Options

Network Time Server Port

1 x RJ45 UTP connector

10/100 Mbps

Timing accuracy: <200 ns to UTC

This UTP network interface option allows the TCG 02-E to function as a Stratum 1 NTP/ SNTP Time Server.

Protocols Supported:

ARP, TCP, ICMP, Telnet, TFTP, DHCP, SNMP, and BOOTP.

IEEE 1588 v2 support

As per Network Time Server above plus:-

PTP (IEEE1588) v2 operation

GrandMaster (GPS) or ordinary clock functions - determined via BMC algorithm

Profile selection: Default or Power

1-step tx, 1-step/ 2-step rx

Layer 2 or Layer 3 mapping

Peer to Peer and End to End delay support

Multicast operation

Typical ordinary clock PPS accuracy (single sub-net) <250 ns

2 Channel Event recording

2 channel event recording with common return that may be driven by TTL logic levels.

Lightning protection kit

Polyphaser DGXZ+06NFNF-A Impulse Suppressor multi-strike weather proofed low throughput energy lightning arrester kit.

Antenna Mounting Bracket

Adjustable 500 mm mounting bracket.

Configuration software

Windows based configuration software is supplied on CD and is also available to be downloaded from the Tekron website. User adjustable options include:

Timing & Synchronization

Worldwide daylight savings and local time configuration using either rule based or fixed date methods.

Options that allow equipment checks prior to full installation and adjustable hold-over times to increase reliability in the case of poor GPS coverage.

Adjustments to compensate for installation parameters such as delay of GPS signal through antenna cable.

Programmable Outputs

IRIG-B (B00x / B22x) time code with selectable IEEE1344 and AFNOR S87-500 extensions

DCF77 time code

User defined pulse sequences:

Repetition rates from 20 ms to 24 hours

Offsets and durations from 10 ms to 24 hours

Resolution is 10 ms; timing accuracy is 100 ns

Serial Strings

NMEA-0183 ZDA

NMEA-0183 RMC

IRIG J-17

Tekron A - F (Six protocols for plug and play compatibility with a wide range of equipment).

Environmental & Electrical

1 x IEC320 power supply (100 - 300 Vdc/ 85 - 264 Vac)

An additional IEC320 power supply can be ordered for redundancy.

Power Drain: 8 W max

Operating temperature: -10 to +65° C

Humidity: To 95% non-condensing

Isolation

Outputs to base unit: 2.5 kV

Power supply to I/O: 3.5 kV

Request a quote

Web: www.tekroninternational.com

Phone: +64 4 566 7722

Fax: +64 4 569 9272

Email: information@tekroninternational.com

Note: The quickest and most effective method to request a quote is through the online quote request form on the Tekron website.

The specifications contained in this document are subject to change without notice.